



DASH NO.	"C"	"AD"
750	19.01	4.63
800	19.51	5.13
850	20.01	5.63

MAXIMUM FACE RUNOUT TO BE .004 TIR
 MAXIMUM PILOT ECCENTRICITY .004 TIR
 PERMISSIBLE SHAFT RUNOUT .002 TIR

WASHGUARD FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE
- 4) GASKETS THROUGHOUT

NO.	REVISION	BY & DATE	TOLERANCES UNLESS SPECIFIED		FINISH	MATERIAL	TITLE	DRAWN	RDW	DATE
			DEC.	INCHES						
02	ADDED PLASTIC PLUG PER ISAAC 08-1811	ARV 5/1/08	.X	±.1			OUTLINE - 140TC FRAME TEFC - RIGID "C"	CHK	SW	1/9/04
01	ADDED 1/2-14 NPT HOLE AT 9 O'CLOCK IN CONDUIT BOX, AND ADDED 1/2-14 PIPE PLUG, PER ECR 83722	BJB 02/04/04	.XX	±.03				APPD	SW	1/9/04
			.XXX	±.005				SCALE	1-2	
			.XXXX	±.0005			REF	PRO20608		
			CHK	ANG	±1/2'		FMF	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT.										
RFP 1/9/04 CAD FILE 028571								SIZE	DRAWING NO.	
DIST								B	028571	
										REV.
										02



ELECTRIC MOTORS
GEARMOTORS
AND DRIVES