



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

						TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN TLB 02-02-1988		
						DEC.	INCHES			CHK	FG 02-04-1988	
						.X	±.1			APPD	ML 02-04-1988	
6	CONVERTED TO AUTOCAD					KL	07-12-2005	.XX	±.03	TITLE OUTLINE		SCALE 1=5
5	REVISED CONDUIT BOX CN 24390					MRB	09-09-1999	.XXX	±.005	360TS & US FR. - DR.PR.		REF
4	REDRAWN ON CADD					TLB	02-02-1988	.XXXX	±.0005	MAT'L		FMF
NO.	REVISION					BY & DATE	CHK	ANG	±7'30"	FINISH		PREV
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE SS509469			SIZE	DRAWING NO. PAGE OF REV.	
DASH	FRAME	B	C	2F	BS	DIST	WA	B	SS509469	6	6	
1400	364TS	13.25	26.50	11.25	5.62							
1500	365TS	14.25	27.50	12.25	6.12							