



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED ON ITS AXIS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

| DASH | FRAME | B | C | 2F | 2FF | BS |
|------|-------|-------|-------|------|-------|------|
| 1050 | 254T | 10.25 | 23.43 | ---- | 8.25 | 4.12 |
| 1225 | 256T | 12.00 | 25.18 | 8.25 | 10.00 | 5.00 |

| DRAWING REVISION | REVISION BY | DATE |
|------------------|-------------|------|
| ECO | APPROVED BY | DATE |
| ECO DESCRIPTION | | |

TOLERANCES UNLESS OTHERWISE SPECIFIED:
 DEC. INCH mm ANGLE
 .X ±0.1 [±2.5] ±7° 30'
 .XX ±0.03 [±0.76]
 .XXX ±0.005 [±0.127]
 .XXXX ±0.0005 [±0.0127]
 REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [.076/.381]
 CORNER FILLETS: .02 [.51]
 MACHINED SURFACES: 200 INCH 5.1 mm/mm

DRAWN BY TVUE
 DATE 12-18-2013
 APPROVED BY TBROWN
 DATE 12-18-2013
 PROCESS/FINISH

REGAL™ Regal Beloit America, Inc.
 DESCRIPTION: **OUTLINE 250T FR. - TEFC - BB - STD.**
 MATERIAL
 DRAWING NUMBER: **SS203002**
 SHEET 1 OF 1