



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

DASH	FRAME	B	C	2F	2FF	2FFF	BS
725	213U	7.00	17.82	5.50	-	-	2.75
875	215U	8.50	19.32	7.00	-	-	3.50
875	213/5U	8.50	19.32	7.00	5.50	5.50	3.50
1000	213U	9.75	20.57	8.25	5.50	5.50	4.12
1000	215U	9.75	20.57	8.25	7.00	7.00	4.12

3	12-12-2000	CHANGE "T" TO "U" CN 30197	CTO		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOL. ON XX±.03 XXX±.005 XXXX±.0005 ANGLES± 7'30"	MAX. SURFACE ROUGHNESS UNLESS OTHERWISE NOTED	DRAWN BY BJJ 06-20-2000 CHKD BY ML 06-21-2000 APPD BY TB 06-22-2000
2	08-09-2000	REVISED OUTLINE TO HAVE C'BOX FROM: SS84236 CN 29200-711	MSG				
1	06-22-2000	NEW DRAWING MU31438	BJW				
REV	DATE	CHANGE	NAME				
PART NAME OUTLINE 210U FR. - TEFC - STEEL C'BOX							

| L | PURCHASED | CADD FILE NO. | SS88189LN

ERROR: syntaxerror
OFFENDING COMMAND: --nostringval--

STACK:

/RS
-dictionary-
/Pscript_WinNT_Compat
-dictionary-