



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	AG	2F	BS	REV	DATE	CHANGE	NAME	PART NAME	DRWG NO
1525	404UC	14.75	35.50	28.62	12.25	6.12	I	03-13-2001	NEW DRAWING	KL	OUTLINE - TAPPED LEAD HOLE	B-SS518333LN
1675	405UC	16.25	37.00	30.12	13.75	6.88					400UC FR. - TEFC	



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
 TOL. ON XX±.03 XXX±.005 XXXX±.0005 ANGLES± 7'30"

MAX. SURFACE ROUGHNESS UNLESS OTHERWISE NOTED

FINISH

MATERIAL

DRAWN BY KL 03-13-2001

CHKD BY DJK 03-13-2001

APPD BY JES 03-13-2001

PURCHASED | DISTRIBUTION WA - LB - WP - LN - BY | CADD FILE NO. SS518333LN

ERROR: undefined
OFFENDING COMMAND: Pscript_WinNT_Comp
STACK: