


- NOTES:
 1. NAMEPLATE TO BE READ FROM C'BOX SIDE OF MOTOR.
 2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180° (EXCEPT AS NOTED.)
 3. DASH 965 TO BE READ FROM OPPOSITE SHAFT END

DASH	FR.	C		BS	MOUNTING
965	213T	18.34		4.80	
1115	213/15T	19.84		6.30	
1240	213/15T	21.09		7.55	F1 ONLY

			TOLERANCES UNLESS SPECIFIED			 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN HLB 07-16-2002
			DEC.	INCHES			CHK DRS 07-18-2002
3	ADDED NOTE 3 & REMOVED GROMMET CN 31848, 31881	DRS 10-21-2002	ML	.X	±.1		APPD TB 07-19-2002
2	REMOVED "BOX CAN BE MOUNTED IN 90 DEG STEPS" FROM NOTES. CN29200-2517	RJM 08-20-2002	JPL	.XX	±.03	TITLE OUTLINE 210 FR. - BB - TS - TEFC - R/S	SCALE 1=5
1	NEW DRAWING	HLB 07-19-2002	TB	.XXX	±.005	MAT'L.	REF
NO.	REVISION	BY & DATE	CHK	ANG	±1/2'	FINISH	FMF
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP	CAD FILE ss88676le			SIZE A
			DIST LB-LE				DRAWING NO. SS88676LE
						PAGE OF	REV. 3